

LITHIONICS BATTERY®

LITHIUM ION IRON PHOSPHATE BATTERY SYSTEMS



MODEL NUMBER:
GT48V150A-8DR-CTRL400

INTERNAL BMS
VERSION



NEVERDIE®

| Item | Description | |
|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|
| Model | GT48V150A-8DR-CTRL400 | |
| Nominal Voltage | 48 | |
| Nominal Capacity | 150 | |
| Nominal Watt Hours | 7200 | |
| Internal Resistance | <300 milliohms | |
| Charge | | |
| Charging temperature range | 32F/0C to 113F/45C | |
| Charge voltage | 54.75 | |
| Recommended float charge voltage(for standby use) | 50.25 | |
| Recommended max charge current* | 75 | |
| Allowed max charge current* | 150 | |
| Discharge | | |
| Discharging temperature range | -4F/-20C to 131F/55C | |
| Operating Voltage Range | 43.5 to 50.25 | |
| Recommended max discharge current* | 150 | |
| Max discharge current* | 225 | |
| Pulse discharge current | 1500 | |
| Discharge cut-off voltage | NeverDie® Power Reserve @ 45.00 Low-Voltage Cut-Off @43.5 | |
| Mechanical | | |
| Dimensions | Length | 23.0" |
| | Width | 13.0" |
| | Height | 13.5" |
| Weight | Approx. 148lbs (67.1kg) | |
| Storage | | |
| Storage Temperature & Humidity Range | < 1 Month | -4~95°F (-20~35°C), 45~75%RH |
| | < 3 Months | 14~86°F (-10~30°C), 45~75%RH |
| | Recommended storage | 59~95°F (15~35°C), 45%RH~75%RH |
| Long Term Storage | If the battery needs to be stored for > 3 months the voltage should be 13.2V (50%SOC), and stored at the recommended storage specifications shown above. Additionally, the battery needs at least one charge & discharge cycle every six months. | |
| Self-discharge rate | Residual capacity | ≤3% per month; ≤15% per year |
| | Reversible capacity | ≤1.5%per month; ≤8% per year |

* Maximum charging and discharging rates apply depending upon the ambient temperature and duty cycle of the system. UL1973 tests of maximum charge and discharge current were performed at 25°C/77°F

INTERNAL NEVERDIE® FEATURES

- miniBMS® Cell/Module Sensors and Microprocessors with Automatic Cell Balancing
- NeverDie® Power Reserve (Spare Fuel) for Hotel Loads and Worry-Free Power for Engine Cranking
- 100% Pure Copper Power Transmission (No Restrictive Nickel, Aluminum, or MOSFETS)
- UL Approved Temperature Protection System
- UL Approved Fully Redundant Protective Safety Circuits
- Over-Charge, Over-Discharge and Short-Circuit Protection (LVC, HVC, SCC)
- Military Grade/Military Approved Hermetically-Sealed UL508 Approved Gas-Filled Pure Silver-Alloy Contactor with Aux-Contact Monitoring Circuit and Internal Arc-Suppression.
- Available NeverDie® Internal Heating Kit: Permits Charging Operations at -20C/-4F Continuous (Most Models...Please Confirm with Factory)
- Pushbutton Storage Operation



ENERGY

150 AMP HOURS

PULSE AMPS: 1500 (1 SEC)

7200 WATT-HOURS

WARNING

- LITHIUM BATTERIES ARE NOT DESIGNED FOR CHARGING IN SUB-FREEZING TEMPERATURES. CONTACT LITHIONICS BATTERY® FOR DETAILS ON OUR COLD WEATHER PACKAGE.
- INSTALLATION: IT IS RECOMMENDED THAT BATTERIES BE INSTALLED CABLE OR TERMINAL SIDE UP.

NOTE: CONTACT LITHIONICS BATTERY® FOR A USER INSTALLATION GUIDE & STORAGE PROCEDURES. FOLLOW THE GUIDE TO ENSURE FITNESS OF USE & WARRANTY.

48V
GT
SERIES